

effluent reduction attainable by the

application of the best available technology economically achievable.

(1) Subpart D (For End-of-Pipe Effluent).

| Pollutant or pollutant property | BAT effluent limitations micrograms per liter (µg/L) | |
|---------------------------------|--|-----------------|
| | Maximum for any one day | Monthly average |
| Acetone | 413 | 178 |
| Acetonitrile | ND | ND |
| n-Amyl Acetate | 3,000 | 1,280 |
| Amyl Alcohol | 3,980 | 1,690 |
| Aniline | 10 | 10 |
| Benzene | 40 | 17 |
| 2-Butanone (MEK) | 202 | 86 |
| n-Butyl Acetate | 500 | 500 |
| n-Butyl Alcohol | ND | ND |
| tert-Butyl Alcohol | 3,980 | 1,690 |
| Chemical Oxygen Demand (COD) | 145,000 | 59,900 |
| Chlorobenzene | ND | ND |
| Chloroform | 22 | 13 |
| Chloromethane | 206 | 87 |
| Cyclohexane | ND | ND |
| o-Dichlorobenzene | ND | ND |
| 1,2-Dichloroethane | 438 | 152 |
| Diethylamine | ND | ND |
| Diethyl Ether | 4,870 | 2,070 |
| N,N-Dimethylacetamide | ND | ND |
| Dimethylamine | ND | ND |
| N,N-Dimethylaniline | 50 | 50 |
| N,N-Dimethylformamide | 45 | 19 |
| Dimethyl Sulfoxide | ND | ND |
| 1,4-Dioxane | 220 | 94 |
| Ethanol | ND | ND |
| Ethyl Acetate | 3,000 | 1,280 |
| Ethylene Glycol | ND | ND |
| Formaldehyde | 1,480 | 623 |
| Formamide | ND | ND |
| Furfural | 3,000 | 1,280 |
| n-Heptane | ND | ND |
| n-Hexane | ND | ND |
| Isobutyraldehyde | 1,370 | 581 |
| Isopropanol | 1,120 | 476 |
| Isopropyl Acetate | 500 | 500 |
| Isopropyl Ether | 4,870 | 2,070 |
| Methanol | 6,660 | ND |
| Methylamine | ND | ND |
| Methyl Cellosolve | ND | ND |
| Methylene Chloride | 1,420 | 357 |
| Methyl Formate | 3,000 | 1,280 |
| Methyl Isobutyl Ketone (MIBK) | 119 | 51 |
| 2-Methylpyridine | 50 | 50 |
| Petroleum Naphtha | 40 | 17 |
| Phenol | 25 | 14 |
| Polyethylene Glycol 600 | 4,870 | 2,070 |
| n-Propanol | 3,980 | ND |
| Pyridine | 10 | 10 |
| Tetrahydrofuran | 15,000 | 4,350 |
| Toluene | 40 | 17 |
| Trichlorofluoromethane | 599 | 322 |
| Triethylamine | ND | ND |
| Xylenes | ND | ND |

(2) [Reserved]

(b) [Reserved]

17. Section 439.45 is amended by revising paragraph (a) introductory text and paragraph (b) to read as follows:

§ 439.45 New source performance standards (NSPS).

(a) Any new source subject to this subpart that was a "new source" under

40 CFR 122.29 prior to [promulgation date of the final rule] must achieve the following new source performance standards until the expiration of the applicable time period specified in 40 CFR 122.29(d)(1), after which the source must achieve the effluent limitations

specified in §§ 439.42, 439.43, and 439.44.

* * * * *

(b) Except as provided in paragraph (a) of this section, any new source subject to this subpart must achieve the following new source performance standards.